



## Dune Tile – Photometric Data

### Photometric Measurements

Total Luminous Flux (lm)	Electrical Power (W)	Luminous Efficacy (lm/W)	Test Distance (m)
923.08	14.29	64.59	8.62

### Electrical Measurements


Power Factor	Power (W)	Voltage (V)	Current (A)	Apparent Power (VA)	Frequency (Hz)	Current THD (%)
0.45	14.29	230.00	0.14	32.20	50.00	192.20

Test Report Number: 961234864  
Test Item Number: WTL 4040 003

### Luminaire Dimensions

Sample Diameter/ Length (mm)	Sample Width (mm)	Sample Height/Depth (mm)	Luminous Diameter/ Length (mm)	Luminous Width (mm)	Luminous Height/Depth (mm)	Luminous C0-plane (mm)	Luminous C90-plane (mm)	Luminous C180-plane (mm)	Luminous C270-plane (mm)
395.00	395.00	130.00	395.00	395.00	100.00	100.00	100.00	100.00	100.00


Isocandela Contour Plot



Minimum Intensity (cd)	Maximum Intensity (cd)
32.44	229.80

Test Report Number: 961234864  
Test Item Number: WTL 4040 003

Polar Plot (cd)



	max plane	0.00				
	max plane	90.00				
	max plane	180.00				
	max plane	270.00				
	max plane	355.00				
	max cone (half)	2.50				
	max cone (half)	0.00				
	max cone (half)	0.00				